



Hamilton All Purpose



Hamilton Drywall Products All Purpose Joint Compound is a light-weight pre-mixed, high performance, drywall compound. It can be used for embedding tape and paper trim and for filling and finishing drywall joints, fasteners, and trims. It has excellent bond, workability and working time, extremely low shrinkage, excellent slip, and superior sandability. It applies very easily and provides a very smooth finished surface with virtually no surface imperfections. Meets ASTM Standard C475.

Standards: All Purpose meets or exceeds ASTM C-475 "Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board".

Job Conditions: Maintain a minimum air, surface and compound temperature of 10° C (50° F) for 48 hours prior to application and until dry and stable.

Surface Preparation: All surfaces must be firm, clean, dry and free of foreign substances. Open spaces between panels or voids of 3mm (1/8") or more should be pre-filled with compound at least 24 hours prior to tape embedding or first coat work. Hamilton Drywall Products Ultra-Fill or Smooth Set Lites are recommended for larger fills.

Mixing: In a clean container mix mechanically to a smooth, creamy consistency, adding more water as required. Add water in 125 ml (1/2 cup) increments to avoid over thinning.

Application: For interior use only. Apply with hand or mechanical tools. Allow compound to dry thoroughly between coats. When sanding, use 180-grit or finer sandpaper or 220-grit mesh cloth. Avoid scuffing gypsum panel paper.

Coverage/Yield: 17 litre carton — Approximate coverage - 45-70 square meters (484-754 square feet). Approximate yield - 17-21 litres depending on application.
18 litre pail — Approximate coverage - 52-81 square meters (562-876 square feet). Approximate yield - 18-22 litres depending on application.

Storage/Shelf Life: Rotate inventory within 90 days of the production date on the package. Store in a dry environment away from freezing, extreme heat and direct sunlight. For best results use within 6 months.

Hamilton Drywall Products Canada
655 West Kent Avenue North, Unit 500
Vancouver, BC, V6P 6T7
(604) 515-0630 • hamiltondp.com

Hamilton Drywall Products USA
295 North Pekin Road
Woodland, WA 98674
(800) 871-4998 • hamiltonnw.com

Submittal Approvals

Job Name:

Contractor:

Date:

Hamilton Drywall Products Canada
655 West Kent Avenue North, Unit 500
Vancouver, BC, V6P 6T7
(604) 515-0630 • hamiltondp.com

Hamilton Drywall Products USA
295 North Pekin Road
Woodland, WA 98674
(800) 871-4998 • hamiltonnw.com