



Hamilton Ready-Tex Ultra



Hamilton Drywall Products Ready-Tex Ultra is a pre-mixed, light weight, aggregate-free, white wall and ceiling texture especially formulated for knock-down texture finishes. Ready-Tex Ultra adheres well to a variety of properly prepared substrates including drywall, plaster, concrete and brick. It can be sprayed to achieve fine, medium, and coarse texture finishes. Ready-Tex Ultra mixes, sprays and atomizes easily, has excellent workability and very good coverage and stand-out/definition.

Job Conditions: _____

Maintain a minimum air, surface and texture material temperature of 10° C (50° F) for 48 hours prior to application and until texture is completely dry.

Surface Preparation: _____

All surfaces must be firm, clean, dry and free of foreign substances. The absorption rate of the surface that Ready-Tex Ultra is applied to may cause variation in the texture pattern. **NEW DRYWALL** should be primed with one or more coats of Hamilton's Prep-Tex Plus prior to texture application. Paint must be completely dry prior to texture application. **CONCRETE** surfaces must be aged at least 60 days prior to texture application. Particular caution should be exercised to determine the presence of efflorescence, dirt, dust, grease, separating and/or bond breaking agents, or a latent layer of cement. After removal of any of the foregoing, any irregularities in the concrete surface should be filled and smoothed with the appropriate Hamilton products.

Mixing: _____

In a clean container mix mechanically to a smooth, creamy consistency, adding more water as required.

Application: _____

For interior use only. Ready-Tex Ultra can be spray applied using a hand held hopper, stator tube or pressure pot machine.

Coverage/Yield: _____

Heavy spray: Approx. 22-45 square meters (240-500 square feet) per 17 litre carton. **Light spray:** Approx. 45-65 square meters (500-700 square feet) per 17 litre carton. Approximate yield per 17 litre carton (adjusted to spray consistency) – 22 litres.

Storage/Shelf Life: _____

Rotate inventory within 90 days of the production date on the package. Store in a dry environment away from freezing, extreme heat and direct sunlight.

Hamilton Drywall Products Canada
655 West Kent Avenue North, Unit 500
Vancouver, BC, V6P 6T7
(604) 515-0630 • hamiltondp.com

Hamilton Drywall Products USA
295 North Pekin Road
Woodland, WA 98674
(800) 871-4998 • hamiltonnw.com

Submittal Approvals

Job Name:

Contractor:

Date:

Hamilton Drywall Products Canada
655 West Kent Avenue North, Unit 500
Vancouver, BC, V6P 6T7
(604) 515-0630 • hamiltondp.com

Hamilton Drywall Products USA
295 North Pekin Road
Woodland, WA 98674
(800) 871-4998 • hamiltonnw.com